















Handle Sets – 30mm Plate

Solid Brass

- 01  Satin Chrome
- 03  Polished Brass
- 04  Antique Brass
- 05  Oil Rubbed Bronze
- 11  Satin Nickel
- 25  Dark Bronze
- 28  Pewter

Zamac

- 01  Satin Chrome
- 5  Dark Bronze
- 6  Black
- 7  White
- 28  Pewter



Colors on this document are graphic representation and may not be an exact match for the actual painted/plated hardware. For color selection, material samples are available on request.

HEAD OFFICE
Ferco Architectural Hardware Inc.
2000, Berlier St.
Laval, QC H7L 4S4
Tel.: 450 973-1437
1 800 355-8810
Fax: 450 973-7661
ferco@ferco.ca
www.ferco.ca

ONTARIO / WESTERN PROVINCES
Tel.: 905 282-9588
1 800 668-5310
Fax: 905 282-9915

UNITED STATES
Tel.: 1 800 927-1097
Fax: 1 888 454-0161

Securing technology for you





GU-SECURY Automatic Lock

SIMPLY CLOSE THE DOOR

European technology in a North American Lock.

By simply closing the door the upper and lower 3/4" (20 mm) latchbolts will instantly engage.

By turning the key from outside or the knob from inside it will engage the 1" central deadbolt and block the top and bottom latchbolts to become a 3-deadbolts locking system.

The Advantages

- 1** The top and bottom 3/4" (20mm) tempered steel latchbolts always engage behind the keepers upon closing the door:
 - give more security
 - give better weather sealing performance
 - help reduce door warpage
- 2** No lifting of the handle to engage locking points
- 2** 1" (25mm) central deadbolt
- 3** 90 degree rotation of thumbturn or US-cylinder engages the deadbolt
- 4** Reversible latch
- 5** High grade 16mm Stainless Steel faceplate for higher corrosion resistance. Radius ends for a clean look and easy installation
- 6** Available in 45, 50 and 60mm backsets for 6' 8" and 8' doors. Extension with additional lock point is available for doors taller than 8'

